

RIGID CORE · UNILIN CLICK

SPC Flooring

Sleek Flooring SPC is a rigid stone-plastic composite floor with an integral IXPE backing layer, locking together on the UNILIN click system for a straightforward, adhesive-free floating installation across wood, stone and marble designs, finished with a 0.55 mm wear layer.

01 PRODUCT CONSTRUCTION & DATA

FORMAT	DIMENSIONS	TOTAL THICKNESS	WEAR LAYER	PACK COVERAGE
Plank	183 × 1227 mm	6 mm total (5 mm SPC core + 1 mm IXPE)	0.55 mm	1.83 m ² / carton
Stone & Marble Tile	305 × 610 mm	6 mm total (5 mm SPC core + 1 mm IXPE)	0.55 mm	1.86 m ² / carton

Installation system: UNILIN click — a floating floor, laid without adhesive, over a suitably prepared subfloor. **Construction:** printed décor film over a rigid SPC core (5 mm) with an integral 1 mm IXPE backing layer, finished with a 0.55 mm wear layer.



UNDERFLOOR HEATING — SUITABLE

Sleek Flooring SPC is suitable for installation over underfloor heating, subject to the heating system operating within the flooring's specified maximum surface temperature. Confirm system operating limits with the heating manufacturer before installation.

02 SUITABLE FOR

RESIDENTIAL	RETAIL	HOSPITALITY	OFFICES	EDUCATIONAL	COMMERCIAL

Led by Design. Made for Homes.

03 TECHNICAL PERFORMANCE

CHARACTERISTIC	STANDARD	RESULT
Wear-layer classification	EN ISO 10874	Domestic 23 · Commercial 33
Reaction to fire	EN 13501-1	B _{fl} -s1
Slip resistance	DIN 51130 / EN 13893	R9 · Class DS
CE marking	EN 14041	Compliant
Quality management	ISO 9001	Manufactured under an ISO 9001 quality system

Residual indentation, furniture-leg, castor-chair, thermal/curl and chemical-resistance results are not reproduced on this sheet pending confirmation directly against the source test certificates — see the accompanying production report.

04 KEY FEATURES

 Click Installation A floating, adhesive-free UNILIN click system for a straightforward installation.	 Scratch & Stain Resistant A 0.55 mm wear layer across every décor, for lasting everyday performance.	 Underfloor Heating Suitable Compatible with underfloor heating within the system's specified operating limits.	 25 / 20-Year Warranty 25-year residential · 20-year commercial limited product warranty (SF-WAR-01).
---	---	---	---

05 DOCUMENTS & FURTHER INFORMATION

Installation guidance: SF-INS-SPC-01 (Sleek Flooring SPC Installation Guide) — in preparation.
 Warranty: SF-WAR-01 (Sleek Flooring Limited Product Warranty) · SF-FRM-WAR-01 (Installation & Warranty Record).
 Full colour range and current stock availability: sleek-flooring.com

Led by Design. Made for Homes.